

AD SRO – AD SROA

MAIN FEATURES

Interface relay modules for safety light curtains with feedback input for EDM, such as EOS4 X, Admiral AX, EOS2 X, Vision VX/VXL/MXL and Janus.

With guided-contact safety relays, 2 NO + 1 NC (AD SRO) or 2 NO contacts (AD SROA).

Additional NC contact line for the monitoring by light curtain (EDM).



TECHNICAL FEATURES

Model	AD SRO	AD SROA
Safety relay outputs	2 NO + 1 NC- 2 A 250 VAC *	2 NO - 2 A 250 VAC
Two-channel inputs for safety light curtains	1	
Response time (ms)	≤ 20	
Power supply (VDC)	24 ± 20%	
Electrical connections	on terminal block	
Operating temperature (°C)	0 to 55	
Protection rating	IP 20 for housing - IP 2X for terminal block	
Fastening	rail fastening according to EN 50022-35 standard	
Dimensions - h x w x d (mm)	101 x 35 x 120	

* In AD SRO safety relay each NO safety output line is interrupted twice by the two relays

ORDERING INFORMATION (for ordering codes see page 226)

Each AD SRO / AD SROA Safety interface includes:

- Multi-language instruction manual complete with CE declaration of conformity



WARNING!

AD SRO and AD SROA modules can only be connected to safety sensors equipped with feedback input for monitoring external relays (EDM): EOS4 X, EOS2 X, Janus, Admiral AX (excluding AX BK models with Blanking), Pharo and Vision VX, VXL and MXL ranges.

Please contact Reer for any other type of application.