

SENSORI INDUTTIVI ANALOGICI - ULTRASONICI

ANALOGUE INDUCTIVE - ULTRASONIC SENSORS

SENSORI INDUTTIVI ANALOGICI Analogue inductive sensors

Diametro <i>Diameter</i>	Lunghezza <i>Housing</i>	Montaggio <i>Installation</i>	Distanza <i>Distance</i>	Conn. <i>Plug</i>	Uscita / Output 0...10V	Uscita / Output 0...10V + 4...20mA
M8	Standard	Sch. / Flush	0...4 mm	Cavo / Cable	AE1/D1-7A	/
				M8	AE1/D1-7F	/
M12	Standard	Sch. / Flush	0...6 mm	Cavo / Cable	/	AM1/D2-5A
				M12	/	AM1/D2-5H
M18	Corto / Short	Sch. / Flush	0...10 mm	Cavo / Cable	/	AK6/D2-5A
				M12	/	AK6/D2-5H

SENSORI AD ULTRASUONI ULTRASONIC SENSORS

Dimensione <i>Dimension</i>	Modello <i>Model</i>	Portata <i>Distance</i>	Uscita <i>Exit</i>	PNP - NO <i>Trimmer</i> 	Uscita analogica <i>Analogue output</i> 0...10V	Uscita analogica <i>Analogue output</i> 4...20mA	2 x PNP - NO+ 1 x 0...10V Teach-in 	2 x PNP - NO+ 1 x 4...20mA Teach-in 
M18	Tasteggio diretto <i>Diffuse reflection</i>	60...300 mm	M12 volante <i>M12 pig tail</i>	SU0/B0-0V	/	/	/	/
			Cavo / <i>Cable</i>	/	SU0/B1-0A	SU0/B2-0A	/	/
		100...600 mm	M12 volante <i>M12 pig tail</i>	SU1/B0-0V	/	/	/	/
			M12	/	SU1/B1-0E	SU1/B2-0E	/	/
		200...1500 mm	Cavo / <i>Cable</i>	/	SU1/B1-0A	SU1/B2-0A	/	/
			M12 volante <i>M12 pig tail</i>	SU2/A0-0V	/	/	/	/
	Riflessione <i>Retroreflective</i>	400...1500 mm*	M12	/	SU2/A1-0E	SU2/A2-0E	/	/
			M12 volante <i>M12 pig tail</i>	SU3/A0-0V	/	/	/	/
M30	Tasteggio diretto <i>Diffuse reflection</i>	300...2500 mm	M12	TU1/C0-0E	TU1/C1-0E	TU1/C2-0E	/	/
		250...2000 mm	M12	/	/	/	TU2/A3-0E	TU2/A4-0E
		350...3500 mm	M12	/	/	/	TU3/C3-0E	TU3/C4-0E
				PNP - NO	PNP - NC	NPN - NO	NPN - NC	
30x20x15 mm	Barriera <i>Through beam</i>	0...300 mm**	Cavo / <i>Cable</i>	UHZ/AP-0A	UHZ/CP-0A	UHZ/AN-0A	UHZ/CN-0A	

* distanza tra sensore e riflettore / distance between sensor and reflector

** distanza tra proiettore e ricevitore / distance between emitter and receiver