

Silver Plus

HMI5104T

**10.4" 65K Color TFT LCD Touchscreen
with advanced features**



- Bright 65,536 (16-Bit) color TFT display
- Built-in Ethernet, serial, USB, and CompactFlash ports
- Support for Allen-Bradley EtherNet/IP and Modbus TCP/IP
- Up to four protocols simultaneously
- TrueType fonts and International characters
- Data logging/Data sampling
- Online/offline simulation
- Multi-language feature
- Alarm and recipe management
- Animation and popup windows
- Most popular PLCs supported
- 2 year warranty

The Silver Series Plus HMI5104T is a rugged graphic operator interface with a high resolution 10.4" diagonal touchscreen TFT display. The nominal 2" depth with port access along the bottom of the OIT makes mounting in tight spots easy. The fanless design means no extra space for cooling is required.

You can easily give your system a professional look with this vivid display, extensive graphics libraries, and the ability to import custom

BMPs, JPGs, or animated GIFs. The HMI5104T can communicate simultaneously with multiple controllers. It is the perfect



operator interface solution for your industrial applications whether process control, packaging, water treatment, building automation, assembly line controls and many others.

The HMI5104T is reliable, affordable, loaded with features, and easy to use. It is another smart solution from the operator interface experts.

**Every Machine
Needs the
Human Touch**



www.maplesystems.com

HMI5104T Specifications

Hardware	
CPU Type	200MHz 32-bit RISC Fanless
Memory	32MB Flash, 64MB DRAM
Ethernet Port	10/100 Base-T (RJ45)
Serial Ports	Com1: RS-232/RS-485, 2 or 4 wire Com2: RS-232 Com3: RS-232/RS-485, 2 wire
USB Interface	3 USB 2.0 Host ports, Type A
CF Card Slot	CompactFlash™, Type II
Sound Output	20-bit Stereo Audio
RTC	Built-in

Display	
Type	10.4" TFT color
Size (WxH)	8.4 x 6.3 inches [213 x 160 mm] 10.4" diagonal
Resolution (pixels)	640 x 480
Brightness (cd/m²)	400
Contrast ratio	300:1
Max Colors	65536 (16 bit)
Viewing Angle (°)	55/65/65/65 (T,B,R,L)
Backlight Longevity	50,000 hrs

Touchscreen	
Type	4-wire analog resistive
Resolution	Continuous
Light Transmission	Above 80%
Lifespan	1 million activations minimum


Environmental	
Operating Temperature	32 ~ 113°F (0 ~ 45°C)
Storage Temperature	-13 ~ 158°F (-25 ~ 70°C)
Relative Humidity	10% ~ 90% (non-condensing)
Shock (operation)	10 to 25Hz (X,Y,Z direction, 2G, 30 minutes)
Ratings	NEMA4/IP65
Certifications	CE, EMI FCC Class A

Functionality	
Networking	Modbus TCP/IP, AB EtherNet/IP, Remote Monitoring
Multiple Port Connectivity	Up to four protocols simultaneously
Data Transfer	Share data between HMIs and PLCs
Data Logging/Sampling	Up to 1000 records Time/Trigger-based
Hardware Options	Mouse, External Keyboard, Memory Storage, Barcode
Windows Fonts	Unicode support International characters
Multiple Languages	Up to 8 languages per object
Security	6 levels, 3 passwords per level Interlock Safety feature Visibility protection
Macros	Math functions, 32-bit Float support
Recipe Management	Up to 32,767 records Index Feature
Alarm Management	Four priority levels Organize by category Real-Time or History
Trending	Up to 8 channels Real-Time or History Time/Date Capture Watch Line Feature
Ease of Use	Popup windows Offline/Online Simulation Extensive Graphics Libraries

Mechanical	
Enclosure	Plastic molding
Dimensions (WxHxD)	11.3 x 8.4 x 2.0 inches [287 x 213 x 50 mm]
Weight	3.4 lbs [1.6 kg]
Mounting	Panel / VESA compatible
Power Requirements	24VDC, 500mA maximum
Warranty	2 years

Order Number	
HMI5104T	10.4" TFT Graphic OIT
HMI5104T-KIT	HMI5104T with software and configuration cable

Specifications may change without notice.



808 134th St. SW
Suite 120,
Everett, WA 98204
425.745.3229
425.745.3429 (fax)
maple@maple-systems.com
www.maplesystems.com